



PROSOCO®

Consolideck®

CONCRETE FLOORING PRODUCTS

# DailyKlean



Consolideck® DailyKlean is a specially designed, fragrance-free, concentrated daily maintenance cleaner for concrete floors to remove most common soiling deposits. It is ideal for concrete floors everywhere, from warehouses and manufacturing plants to schools, stores, hospitals, restaurants and more. Used as part of a comprehensive maintenance program, fragrance-free DailyKlean helps ensure the highest appearance and performance standards for all indoor concrete flatwork. Though DailyKlean is specifically made for floors treated with Consolideck® LS®, LS/CS® or Blended Densifier, it's perfect for almost any concrete floor.

Recognized by the EPA's Safer Choice program, DailyKlean is formulated to be safer for workers and the environment. The solution also offers more positive environmental and human health characteristics than conventional cleaning formulations.

## TYPICAL TECHNICAL DATA

FORM	Colorless, cloudy liquid
SPECIFIC GRAVITY	0.999
pH	8.6
WT/GAL	8.32 lbs
ACTIVE CONTENT	not applicable
TOTAL SOLIDS	not applicable
VOC CONTENT	0
FLASH POINT	>200° F (>93° C) ASTM D 3278
FREEZE POINT	31° F (-1° C)
SHELF LIFE	2 years in tightly sealed, unopened container

## REGULATORY COMPLIANCE

### VOC Compliance

Consolideck® DailyKlean is compliant with all national, state, district, consumer and institutional product VOC regulations.

## ADVANTAGES

- **Recognized by the EPA's Safer Choice program.**
- **Contains no phosphates, hazardous solvents or environmentally harmful surfactants.**
- **Fragrance free. Dye free. Readily biodegradable. Low Toxicity.**
- **Maintains concrete floor shine.**
- **Removes most common soiling.**
- **Flexible dilution for both surface and deep cleaning.**
- **Concentrated for economy of storage and transport.**
- **No rinsing needed for routine surface cleaning of floors.**
- **Ideal for auto scrubbers.**
- **Recommended for use with Brightwell® High Flow ECOMIX COMPACT dispenser unit.**

## Limitations

- May not remove some embedded stains.
- Does not contain lithium silicate. Has no hardening/densifying effect.

## SAFETY INFORMATION

Always read full label and SDS for precautionary instructions before use. Use appropriate safety equipment and job-site controls during application and handling.

**24-Hour Emergency Information:  
INFOTRAC at 800-535-5053**



# Product Data Sheet Consolideck® DailyKlean

## PREPARATION

Sweep or vacuum to remove loose materials from the surface to be cleaned. Pre-clean oil spots or other deep stains with the appropriate PROSOCO® product. Call Customer Care at 800-255-4255 for recommendations.

## Surface and Air Temperatures

Cleaning effectiveness is reduced when surface and air temperatures fall below 50°F (10°C).

Do not apply at temperatures below 40°F (4°C).

## Equipment

Apply using a mop or auto scrubber.

Use soft brushes/pads with auto scrubbers. Never use aggressive brushes or pads on polished concrete.

## Storage and Handling

Store in a cool, dry place. Always seal container after dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperatures of 45–100°F (7–38°C). Do not double stack pallets. Dispose of unused product and container in accordance with local, state and federal regulations.

## APPLICATION

Read “Preparation” and the Safety Data Sheet before use. **ALWAYS TEST** a small area of each surface to confirm suitability, coverage rate and desired results before beginning overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application. Let surface dry thoroughly before inspection.

## Dilution & Mixing

Do not use dilutions stronger than 4-ounces cleaner concentrate to 1-gallon of fresh water. Always use the mildest effective dilution possible.

### Normal Cleaning

dilute 1 oz of cleaner per 1-gal fresh water

### Deep Cleaning

dilute 2 oz of cleaner per 1-gal fresh water

*For use with a Brightwell® High Flow ECOMIX COMPACT dispenser unit:*

Setting I for High Flow

Dilution Ratio of 128:1 at 1-oz/gallon  
(8 mL/liter)

When set properly, Brightwell® High Flow ECOMIX Compact dispenser’s chemical dilution dial will show the letter I at the top (in the 12:00 position).

Read and follow all information and instructions included with the dispenser unit.

For spot cleaning heavily soiled areas, begin testing DailyKlean at a dilution of 2-ounces of cleaner concentrate to 1-gallon of fresh water.

## Application Instructions

1. Apply with a mop or automatic scrubber.
2. After routine surface cleaning, rinsing the concrete floor is not necessary. Mop up spent cleaner and dissolved contaminants, or vacuum up with auto scrubber.

After deep-cleaning, or for cleaning in food processing areas, rinse well with fresh water. Do not let puddles or concentrated cleaner dry on the floor. Mop up rinse water, or vacuum up with auto scrubber.

3. Buff the cleaned floor with a white pad to increase the shine.

## Cleanup

Clean tools and equipment using fresh water.

## Maintenance

Use DailyKlean as part of a comprehensive maintenance program that includes deep cleaning with PROSOCO’s LSKlean at least once a week.

For concrete floors regularly maintained with auto scrubbers, see PROSOCO’s DailyKlean ULTRA 15 or DailyKlean ULTRA 30 for easy dilution. The same ease of dilution is available for deep cleaning with LSKlean ULTRA 15 and LSKlean ULTRA 30.

PROSOCO LSKlean and DailyKlean are recommended for use with the Brightwell® High Flow ECOMIX COMPACT dispenser unit. Contact PROSOCO Customer Care for ordering information.

## WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions

# Product Data Sheet Consolideck® DailyKlean

and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty,

negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

## **CUSTOMER CARE**

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care – technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our website at [prosoco.com](http://prosoco.com), for the name of the PROSOCO representative in your area.

