



PROSOCO®

# Consolideck®

CONCRETE FLOORING PRODUCTS

## Defoamer

Consolideck® Defoamer is an effective, fast-acting foam preventer intended for use in auto-scrubber and other liquid recovery tanks.

Consolideck® Defoamer was developed to help control the foam generated while using products like Consolideck® First Cut and First Cut with Densifier.

### SAFETY INFORMATION

Always read full label and SDS for precautionary instructions before use. Use appropriate safety equipment and job site controls during application and handling.

**24-Hour Emergency Information:**  
INFOTRAC at 800-535-5053

### ADVANTAGES

- Controls foam and stops build-up of foam in auto-scrubber recovery tanks and extractor tanks, reducing time to empty tanks.
- Slightly thickened to allow Defoamer to cling to tools and hose assemblies.
- Helps protect machinery from foam overflow.

### TYPICAL TECHNICAL DATA

<b>FORM</b>	Light tan, opaque liquid mild odor
<b>SPECIFIC GRAVITY</b>	1.00
<b>pH</b>	9.80
<b>WT/GAL</b>	8.32 lbs
<b>ACTIVE CONTENT</b>	not applicable
<b>TOTAL SOLIDS</b>	not applicable
<b>VOC CONTENT</b>	not applicable
<b>FLASH POINT</b>	>200° F (>93° C) ASTM D3278
<b>FREEZE POINT</b>	32° F (0° C)
<b>SHELF LIFE</b>	1 year in tightly sealed, unopened container

### REGULATORY COMPLIANCE

#### VOC Compliance

Consolideck® Defoamer is compliant with all national, state and district VOC regulations.

# Product Data Sheet

## Consolideck® Defoamer

### PREPARATION

Protect people, vehicles, property, plants and all adjacent or nearby surfaces from product, splash and wind drift.

Do not allow product to get directly on to hard surface floors as it may leave the floor slippery.

### Equipment

For use in auto-scrubber recovery tanks and other liquid recovery tanks. Ensure equipment in clean and well maintained per manufacturer instructions.

### Storage and Handling

Store in a cool, dry place. Keep tightly closed when not dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperature of 45–100°F (7–38°C). Do not double stack pallets. Dispose of unused product and container in accordance with local, state and federal regulations.

### APPLICATION

Read “Preparation” and the Safety Data Sheet before use. **ALWAYS TEST** a small area of each surface to confirm suitability, coverage rate and desired results before beginning overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application. Let surface dry thoroughly before inspection.

### Dilution & Mixing

Apply as packaged. Do not dilute or alter. Mix well before use.

### Use Instructions

**CAUTION:** Do not allow product to get directly on to hard surface floors as it may leave the floor slippery. If spill does occur, remove product as soon as possible by scrubbing the floor with the appropriate Consolideck® cleaner, such as DailyKlean or LSKlean, and allow to dry thoroughly.

1. Use 2 to 6 fluid ounces of Defoamer for every 15 gallon capacity of recovery tank.
2. Consolideck® Defoamer may be added directly to recovery tank or by vacuuming through hose assembly:
  - a. *For adding to recovery tank:* add appropriate amount of defoamer directly to clean recovery tank.

- b. *For adding through vacuum hoses:* disconnect vacuum hose from squeegee assembly and place hose into container with required amount of Defoamer and vacuum into recovery tank.

3. Additional Defoamer may be used depending on amount of foam generated in recovery tank.

### Cleanup

Clean tools and equipment with fresh water.

### WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

### CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care – technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our website at prosoco.com, for the name of the PROSOCO representative in your area.