



PROSOCO®

# Enviro Klean®

NEXT GENERATION CLEANERS

## OverCoat®

Enviro Klean® OverCoat® is a specially designed protective paper film. Press OverCoat® paper by hand onto freshly applied coatings of extended-contact gel- and paste-consistency paint and coating removers and cleaners. It adheres to and covers the gel or paste, protecting passersby from accidental contact, as well as insulating the chemical.

In addition, OverCoat® keeps the cleaner moist by reducing evaporation, enhancing and prolonging performance. OverCoat® is easily applied. It's removed and disposed of with the spent cleaner.

### ADVANTAGES

- Protects people from accidental contact with applied cleaners and paint removal products.
- Keeps cleaners and paint strippers moist, prolonging and enhancing performance.
- No special tools or equipment required – apply by hand and remove with a taping knife or trowel and dispose of spent cleaner/paint stripper according to product instructions.

### Limitations

- Not for use with water-thin cleaners or strippers.
- Use only with recommended PROSOCO extended-contact products.

### REGULATORY COMPLIANCE

#### VOC Compliance

Enviro Klean® OverCoat® is compliant with all national, state and district VOC regulations.

### TYPICAL TECHNICAL DATA

<b>FORM</b>	Bleached medium-grade specialty paper
<b>SPECIFIC GRAVITY</b>	not applicable
<b>pH</b>	not applicable
<b>WT/GAL</b>	30# paper
<b>ACTIVE CONTENT</b>	not applicable
<b>TOTAL SOLIDS</b>	not applicable
<b>VOC CONTENT</b>	not applicable
<b>FLASH POINT</b>	not applicable
<b>FREEZE POINT</b>	not applicable
<b>SHELF LIFE</b>	not applicable

### SAFETY INFORMATION

Always read full label and SDS for precautionary instructions before use. Use appropriate safety equipment and job site controls during application and handling.

**24-Hour Emergency Information:**  
**INFOTRAC at 800-535-5053**

# Product Data Sheet

## Enviro Klean® OverCoat®

### PREPARATION

Protect people, vehicles, property, plants and all surfaces not set for paint stripping or cleaning from pastes, paste residue, rinse, fumes and wind drift. Test and protect if needed. Protect/divert auto and pedestrian traffic. Always maintain adequate ventilation when working inside.

### APPLICATION

Read “Preparation” and the Safety Data Sheet before use. **ALWAYS TEST** Enviro Klean® OverCoat® with each type of PROSOCO product to be used. Test OverCoat® and product on each type of surface, coating or stain. Test for suitability, dwell-time and results, using the following application instructions.

#### Product Format

Enviro Klean® OverCoat® is available in:

##### Rolls

- 7.2 inches x 300 feet
- 12 inches x 300 feet

##### Sheets

- 36 inches x 36 inches

#### Application Instructions

1. Apply PROSOCO stripper or cleaner following all label instructions and safety precautions.
2. Cover applied product with sheets of OverCoat®.
3. Rub gently to remove air pockets and ensure smooth, overall adhesion.
4. Let product and OverCoat® dwell. Dwell time should be based upon testing.
5. Follow instructions on cleaner label for removal. Usually this involves inserting a spatula, trowel or scraper under the edge of the paper – and through the paste – then lifting and removing gel/paste, dissolved paint or coating, and paper.
6. Follow stripper/cleaner instructions for surface neutralization or post-stripping clean down, if required.

#### Cleanup

Dispose of paper, spent cleaner and dissolved coatings/contaminants according to local, state and federal regulations.

### WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job

conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO’s liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

### CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care – technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at [www.prosoco.com](http://www.prosoco.com), for the name of the PROSOCO representative in your area.

### BEST PRACTICES

Not for use with water-thin cleaners or strippers. Use only with recommended PROSOCO extended-contact products.

Dispose of paper, spent cleaner and dissolved coatings/contaminants according to local, state and federal regulations.

By itself, Enviro Klean® OverCoat® will not release or otherwise result in exposure to a hazardous chemical. Refer to the Product Data and SDS for health hazard and safety information for cleaners and strippers used with OverCoat.

Never go it alone. If you have problems or questions, contact your local PROSOCO distributor or field representative. Or call PROSOCO technical Customer Care, toll-free, at 800-255-4255.