

SAFETY DATA SHEET



PROSOCO
Revision Number 2

Issuing Date 04-Jan-2016

Revision date 29-May-2025

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name PROSOCO® DuraSheen

Other means of identification

Product Code(s) 46032

UN number UN1866

Recommended use of the chemical and restrictions on use

Recommended use Restricted to professional users.

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

PROSOCO, Inc.
3741 Greenway Circle
Lawrence, Kansas 66046

Emergency telephone number

8:00 AM – 5:00 PM CST Monday-Friday 785-865-4200

NON-BUSINESS HOURS (INFOTRAC) 800-535-5053

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration hazard	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Danger

Hazard statements

Causes skin irritation
Causes serious eye irritation
May cause genetic defects
May cause cancer
Suspected of damaging fertility or the unborn child
May cause respiratory irritation
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Flammable liquid and vapor

**Appearance** clear**Physical state** Liquid**Odor** Solvent**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Wear eye/face protection
 Do not breathe dust/fume/gas/mist/vapors/spray
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/ and /lighting equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 If skin irritation occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

- May be harmful if swallowed
- May be harmful in contact with skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%	Trade Secret
Solvent Naptha (petroleum) light aromatic	64742-95-6	30 - 60	*
Trimethybenzenes, all isomers	25551-13-7	15 - 40	*

1,2,4-trimethylbenzene	95-63-6	10 - 30	*
propylbenzene	103-65-1	7 - 13	*
1,3,5 Trimethylbenzene	108-67-8	7 - 13	*
Xylene	1330-20-7	3 - 7	*
Cumene	98-82-8	3 - 7	*
1,2,3-Trimethyl benzene	526-73-8	3 - 7	*
Styrene	100-42-5	1 - 5	*
Ethylbenzene	100-41-4	1 - 5	*

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a physician.
Ingestion	Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms Causes eye and skin irritation. May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO₂). Water spray (fog). Alcohol resistant foam.

Unsuitable Extinguishing Media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Hazardous combustion products Carbon oxides. Nitrogen oxides (NO_x).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Remove all sources of ignition. Evacuate personnel to safe areas. Pay attention to flashback. Take precautionary measures against static discharges. Keep people away from and upwind of spill/leak.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Use clean non-sparking tools to collect absorbed material. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on safe handling Use personal protective equipment as required. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep out of the reach of children. Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled containers. Keep away from heat.

Incompatible materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Trimethylbenzenes, all isomers 25551-13-7	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³	
1,2,4-trimethylbenzene 95-63-6			TWA: 25 ppm TWA: 125 mg/m ³
1,3,5 Trimethylbenzene 108-67-8			TWA: 25 ppm TWA: 125 mg/m ³
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³
1,2,3-Trimethyl benzene 526-73-8			TWA: 25 ppm TWA: 125 mg/m ³
Styrene	STEL: 20 ppm	TWA: 100 ppm	IDLH: 700 ppm

100-42-5	TWA: 10 ppm	(vacated) TWA: 50 ppm (vacated) TWA: 215 mg/m ³ (vacated) STEL: 100 ppm (vacated) STEL: 425 mg/m ³ Ceiling: 200 ppm	TWA: 50 ppm TWA: 215 mg/m ³ STEL: 100 ppm STEL: 425 mg/m ³
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Solvent
Appearance	clear	Odor threshold	No information available
Color	colorless		
Property	Values	Remarks • Method	
pH	Not Applicable		
Melting point / freezing point °F	No information available		
Boiling point / boiling range	No information available		
Flash point	59 °C / 138 °F		
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limit in Air			
Upper flammability limit:	No information available		
Lower flammability limit:	No information available		
Vapor pressure	No information available		
Vapor density	No information available		
Specific gravity	0.92		
Water solubility			
Solubility in other solvents	No information available		
Partition coefficient	No information available		
Autoignition temperature	No information available		
Decomposition temperature	No information available		

Kinematic viscosity No information available
Dynamic viscosity No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation Avoid breathing vapors or mists.

Eye contact Avoid contact with eyes.

Skin Contact Avoid contact with skin.

Ingestion Do not taste or swallow.

Component Information

Chemical name	LD50/Oral	LD50/Dermal	Inhalation LC50
Solvent Naptha (petroleum) light aromatic 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Trimethybenzenes, all isomers 25551-13-7	= 8970 mg/kg (Rat)		
1,2,4-trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
propylbenzene 103-65-1	= 6040 mg/kg (Rat)		= 65000 ppm (Rat) 2 h
1,3,5 Trimethylbenzene 108-67-8			= 24 g/m ³ (Rat) 4 h
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	> 3577 ppm (Rat) 6 h
Styrene 100-42-5	= 1000 mg/kg (Rat)	> 2000 mg/kg (Rat)	= 11.7 mg/L (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Irritating to eyes and skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity May cause genetic defects.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Cumene 98-82-8	-	Group 2B	Reasonably Anticipated	X
Styrene 100-42-5	A3	Group 2A	Reasonably Anticipated	X
Ethylbenzene 100-41-4	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity May damage fertility or the unborn child.
STOT - single exposure May cause respiratory irritation.
STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.
Chronic toxicity Avoid repeated exposure. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Contains a known or suspected reproductive toxin.
Target organ effects blood, central nervous system, Eyes, liver, Reproductive System, Respiratory system, Skin.
Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	4285 mg/kg
ATEmix (dermal)	2712 mg/kg mg/l
ATEmix (inhalation-dust/mist)	5.4 mg/l
ATEmix (inhalation-vapor)	362 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Solvent Naptha (petroleum) light aromatic 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	-	6.14: 48 h Daphnia magna mg/L EC50
Trimethylbenzenes, all isomers 25551-13-7	-	7.72: 96 h Pimephales promelas mg/L LC50 flow-through	-	-
1,2,4-trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	-	6.14: 48 h Daphnia magna mg/L EC50
1,3,5 Trimethylbenzene 108-67-8	-	3.48: 96 h Pimephales promelas mg/L LC50	-	-
Xylene 1330-20-7	-	13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50	-	0.6: 48 h Gammarus lacustris mg/L LC50 3.82: 48

		flow-through 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50		h water flea mg/L EC50
Cumene 98-82-8	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	-	7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static 0.6: 48 h Daphnia magna mg/L EC50
Styrene 100-42-5	0.15 - 3.2: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 0.46 - 4.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 0.72: 96 h Pseudokirchneriella subcapitata mg/L EC50 1.4: 72 h Pseudokirchneriella subcapitata mg/L EC50	19.03 - 33.53: 96 h Lepomis macrochirus mg/L LC50 static 3.24 - 4.99: 96 h Pimephales promelas mg/L LC50 flow-through 58.75 - 95.32: 96 h Poecilia reticulata mg/L LC50 static 6.75 - 14.5: 96 h Pimephales promelas mg/L LC50 static	-	3.3 - 7.4: 48 h Daphnia magna mg/L EC50
Ethylbenzene 100-41-4	1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 9.6: 96 h Poecilia reticulata mg/L LC50 static	-	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
1,2,4-trimethylbenzene 95-63-6	3.63
propylbenzene 103-65-1	3.68
Xylene 1330-20-7	2.77 - 3.15

Cumene 98-82-8	3.7
Styrene 100-42-5	2.95
Ethylbenzene 100-41-4	3.2

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

14. TRANSPORT INFORMATION

DOT Not regulated (If shipped in NON BULK packaging by ground transport)

UN number UN1866

UN proper shipping name Resin Solution

Transport hazard class(es) 3

Packing group III

UN number UN1866

UN proper shipping name Resin Solution

Transport hazard class(es) 3

Packing group III

UN number UN1866

UN proper shipping name Resin Solution

Transport hazard class(es) 3

Packing group III

Marine pollutant This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
1,2,4-trimethylbenzene - 95-63-6	95-63-6	10 - 20	1.0
Cumene - 98-82-8	98-82-8	1 - 5	0.1
Xylene - 1330-20-7	1330-20-7	1 - 5	1.0
Ethylbenzene - 100-41-4	100-41-4	.1 - 1	0.1
Styrene - 100-42-5	100-42-5	.1 - 1	0.1

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	X
Styrene 100-42-5	1000 lb	-	-	X
Ethylbenzene 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Cumene 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Styrene 100-42-5	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Ethylbenzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Cumene - 98-82-8	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen
Styrene - 100-42-5	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Trimethylbenzenes, all isomers 25551-13-7	X	X	X
1,2,4-trimethylbenzene 95-63-6	X	X	X
propylbenzene 103-65-1	X	X	X

Xylene 1330-20-7	X	X	X
Cumene 98-82-8	X	X	X
Ethylbenzene 100-41-4	X	X	X
Styrene 100-42-5	X	X	X

16. OTHER INFORMATION

NFPA	Health hazards 2	Flammability 2	Instability 0	Physical and chemical properties -
HMIS	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection X

Prepared By Regulatory Department
Issuing Date 04-Jan-2016
Revision date 29-May-2025
Revision Note

SDS sections updated 2 3 8 9 11 14 15
 For product produced after May 15, 2025

Disclaimer

The information contained on the Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

End of Safety Data Sheet