JOB NAME

CUSTOMER

UNIT DESC/WEIGHT

COLOR CODE

DRY BLOCK

RUN DATE

ATTENTION!



These block are made with natural aggregates and are sold as is. They have passed inspection and meet the specifications required. Usage of this product constitutes acceptance. If you have any questions regarding this product, please contact the manufacturer immediately.

Some color variation between blocks is normal and any variation should be distributed evenly through the wall when laying block.

WARNING

DO NOT CLEAN BLOCK WITH MURIATIC ACID! Use a cleaner and weatherproofer made specifically for this block and follow the manufacturer's recommendations!

BURNISHED CUSTOM MASONRY CLEANER

For best overall appearance and color uniformity

Weatherproof these blocks with: SURE KLEAN>

CUSTOM MASONRY SEALER

For best weather resistance



4626 N. 42nd Ave. Phoenix, AZ. 85019 (800) 233-1924 ● www.trenwyth.com



Pressure rinse with 500 to 1500 psi at a water flow rate of 4 to 8 gallons per minute and a 15° to 40° fan spray tip. Reduce water pressure to avoid damage to delicate masonry.

Manufacturer's recommendations

post-construction cleandown weatherproofing

WARNING

DO NOT CLEAN BLOCK WITH MURIATIC ACID!

Use a cleaner and weatherproofer made specifically for this block. follow the manufacturer's recommendations!

Clean these blocks with: SURE KLEAN? BURNISHED CUSTOM

MASONRY CLEANER

For best overall appearance and color uniformity

- Softens excess mortar and job dirt on hard-toclean concrete brick.
- Safe for use on concrete brick and cast stone.
- Won't etch mortar joints.
- Enhances color depth and uniformity
- Rinses clean without streaking

Weatherproof these blocks with: >SURE KLEAN?

CUSTOM MASONRY SEALER

For best weather resistance

- Controls rainwater penetration through exterior masonry and concrete walls.
- Low odor
- Treated surfaces resist penetration of many types of graffiti.
- Simplifies graffiti removal.
- Helps control efflorescence, mildew and other moisture-related stains.
- Treated surfaces exhibit excellent surface beading and withstand exposure to sunlight and extreme temperatures.



Laboratory testing has identified the above products as most effective on and compatible with the concrete block listed in this catalog. For free copies of the test results, product literature or other information related to the care of this block, contact PROSOCO Customer Care toll-free at (800) 255-4255. Or visit PROSOCO's website at www.prosoco.com.



4626 N. 42nd Ave. Phoenix, AZ. 85019 (800) 233-1924 • www.trenwyth.com