

**Important:** These bricks are sold as is. They have been inspected and graded to our standards for this particular type brick. Please carefully examine them to determine if they meet your requirements. Once they have been placed in the wall, they become the property of the purchaser, after which no adjustment will be made by Columbus Brick Company.

When laying brick distribute color range evenly throughout the wall. Lay brick from several packages at one time.

Columbus Brick Company will not be liable for problems resulting from improper masonry construction details, including flashing and weepholes, or improper workmanship.

**CLEANING:** As with any sandface or antique coated brick, cleaning may change the appearance of the finished wall. **DO NOT USE MURIATIC ACID, WIRE OR STIFF BRUSHES, OR HIGH-PRESSURE SPRAYERS.**

For best results, keep brick *relatively* dry prior to laying. Keep the brickwork as clean as possible during laying. Brush off excess mortar with soft brush while the brick work progresses. Remove larger mortar particles with nonmetallic scrapers, if necessary.

In case of extreme mortar accumulations, certain proprietary cleaners such as SURE KLEAN® VANA TROL® (PROSOCO) may be used with caution at a 1:8 ratio of water solution. Follow specific instructions.

*Always test a small area before proceeding.*

For additional cleaning instructions, please contact our office: (662) 328-4931.

**WARNING:** The dust generated from dry sawing brick may contain silica and may be a potential health problem for the lungs, although we are aware of no scientific evidence to support this conclusion. Wet sawing is recommended.



---

# COLUMBUS BRICK COMPANY

SINCE 1890

Queen Run # 2-071404

# Jefferson Manor

*A Genuine Papercut Brick*

[WWW.COLUMBUSBRICK.COM](http://WWW.COLUMBUSBRICK.COM)