#### **USE CONSTITUTES ACCEPTANCE**

Important: These bricks are sold as is. They have been inspected and graded to our standards for this particular type brick. Please carefully examine them to determine if they meet your requirements. Once they have been placed in the wall, they become the property of the purchaser, after which no adjustment will be made by Louisville Brick Company.

When laying brick distribute color range evenly throughout the wall. Lay brick from several packages at one time.

Louisville Brick Company will not be liable for problems resulting from improper masonry construction details, including flashing and weepholes, or improper workmanship.

For best results, keep brick relatively dry prior to laying. Keep the brickwork as clean as possible during laying. Brush off excess mortar with soft brush while the brick work progresses. Remove larger mortar particles with nonmetallic scrapers, if necessary.

CLEANING: As with any sandface or antique coated brick, cleaning may change the appearance of the finished wall. DO NOT USE MURIATIC ACID, WIRE OR STIFF BRUSHES, OR HIGH-PRESSURE SPRAYERS.


In case of extreme mortar accumulations, certain proprietary cleaners such as SURE KLEAN® VANA TROL® (PROSOCO) may be used with caution at a 1:8 ratio of water solution. Follow specific instructions. Always test a small area before proceeding.

WARNING: The dust generated from dry sawing brick may contain silica and may be a potential health problem for the lungs, although we are aware of no scientific evidence to support this conclusion. Wet sawing is recommended.









MANUFACTURERS OF BETTER BUILDING BRICK

### **OLD BIRMINGHAM**

**Cube Count: 520** 



Size: Queen

WWW.LOUISVILLEBRICK.COM

#### **USE CONSTITUTES ACCEPTANCE**

Important: These bricks are sold as is. They have been inspected and graded to our standards for this particular type brick. Please carefully examine them to determine if they meet your requirements. Once they have been placed in the wall, they become the property of the purchaser, after which no adjustment will be made by Louisville Brick Company.

When laying brick distribute color range evenly throughout the wall. Lay brick from several packages at one time.

Louisville Brick Company will not be liable for problems resulting from improper masonry construction details, including flashing and weepholes, or improper workmanship.

For best results, keep brick relatively dry prior to laying. Keep the brickwork as clean as possible during laying. Brush off excess mortar with soft brush while the brick work progresses. Remove larger mortar particles with nonmetallic scrapers, if necessary.

CLEANING: As with any sandface or antique coated brick, cleaning may change the appearance of the finished wall. DO NOT USE MURIATIC ACID, WIRE OR STIFF BRUSHES, OR HIGH-PRESSURE SPRAYERS.


In case of extreme mortar accumulations, certain proprietary cleaners such as SURE KLEAN® VANA TROL® (PROSOCO) may be used with caution at a 1:8 ratio of water solution. Follow specific instructions. Always test a small area before proceeding.

WARNING: The dust generated from dry sawing brick may contain silica and may be a potential health problem for the lungs, although we are aware of no scientific evidence to support this conclusion. Wet sawing is recommended.





# LOUISVILLE BRICK CO., INC.



MANUFACTURERS OF BETTER BUILDING BRICK

## SOUTHAVEN

**Cube Count: 520** 



Size: Queen

WWW.LOUISVILLEBRICK.COM