



Basalite Concrete Products

Dixon, CA

Executive Summary

Project No. 1808-08

Ten CMUs (2 Smooth, 2 Split Face, 2 Ribbed, 2 WR Smooth, 2 WR Ground Face) were submitted to AMT Laboratories by PROSOCO, Inc. with a request to determine the most appropriate new construction cleaner. Additionally, the effectiveness of water repellent and graffiti resistance products suitable for vertical concrete was evaluated.

The laboratory report (1808-08 PTP Basalite Concrete Products) provides information about the PROSOCO® products tested and descriptions of the test methods. The report includes test results as well as conclusions and recommendations. Recommendations are also provided in the chart below.

Recommendations:

Sample	New Construction Cleaning	Water Repellency	Graffiti Resistance
"225 Smooth"	Enviro Klean® Safety Klean (1:2) or (1:3) OR Sure Klean® Light Duty Concrete Cleaner (1:2) or (1:3)	Sure Klean® Weather Seal Blok-Guard® & Graffiti Control Ultra 15 (Recommended if moderate color enhancement is desired) OR Sure Klean® Weather Seal Blok-Guard® & Graffiti Control II (Recommended if slight color enhancement is desired) OR T2537 Saltguard® VOC (Recommended if slight color enhancement is desired) OR Sure Klean® Weather Seal Siloxane WB Concentrate (1:9) (Recommended if slight color enhancement is desired)	<p style="text-align: center;">Graffiti Repellent</p> ¹ Sure Klean® Weather Seal Blok-Guard® & Graffiti Control Ultra 15 (Recommended if moderate color enhancement is desired) OR ² Sure Klean® Weather Seal Blok-Guard® & Graffiti Control II (Recommended if slight color enhancement is desired) <p style="text-align: center;">Graffiti Removers</p> Defacer Eraser® Graffiti Remover OR Enviro Klean® SafStrip® 8
"225 Split Face"	Enviro Klean® Safety Klean (1:2) or (1:3)		
"225 Ribbed"	Sure Klean® Light Duty Concrete Cleaner (1:2) or (1:3)	Sure Klean® Weather Seal Blok-Guard® & Graffiti Control Ultra 15 (Recommended if moderate color enhancement is desired) OR Sure Klean® Weather Seal Blok-Guard® & Graffiti Control II (Recommended if slight color enhancement is desired) OR T2537 Saltguard® VOC (Recommended if slight color enhancement is desired)	
"225 WR Smooth"	Sure Klean® Light Duty Concrete Cleaner (1:2) or (1:3)	Sure Klean® Weather Seal Blok-Guard® & Graffiti Control Ultra 15 (Recommended if moderate color enhancement is desired) OR Sure Klean® Weather Seal Blok-Guard® & Graffiti Control II (Recommended if slight color enhancement is desired) OR T2537 Saltguard® VOC (Recommended if slight color enhancement is desired) OR Sure Klean® Weather Seal Siloxane WB Concentrate (1:9) (Recommended if slight color enhancement is desired)	
"225 WR Ground"	Sure Klean® Custom Masonry Cleaner (1:4) or (1:6) OR Enviro Klean® Safety Klean (1:2) or (1:3) OR Sure Klean® Light Duty Concrete Cleaner (1:2) or (1:3)		
"345 Smooth"	Sure Klean® Light Duty Concrete Cleaner (1:2) or (1:3)		
"345 Split Face"	Enviro Klean® Safety Klean (1:2) or (1:3)		
"345 Ribbed"	Sure Klean® Light Duty Concrete Cleaner (1:2) or (1:3)		
"345 WR Smooth"	Sure Klean® Light Duty Concrete Cleaner (1:2) or (1:3)		
"345 WR Ground"	Sure Klean® Custom Masonry Cleaner (1:4) or (1:6) OR Enviro Klean® Safety Klean (1:2) or (1:3) OR Sure Klean® Light Duty Concrete Cleaner (1:2) or (1:3)		

NOTE: "1" indicates the most effective treatment and "2" indicates the second most effective treatment.

Apply all products in accordance with the manufacturer's recommendation provided on container labels and product data sheets. On-site testing should be conducted to determine the most appropriate product and procedures for a particular project. See product literature for additional application and product information.