



# Sure Klean®

CLEANING & PROTECTIVE TREATMENTS

## Liquid Marble Cleaner

Sure Klean® Liquid Marble Cleaner is a non-acidic, phosphate-free, low-odor, orange-colored gel designed for the cleaning, restoration and maintenance of polished stonework or glazed masonry. Liquid Marble Cleaner loosens and dissolves surface dirt, carbon buildup and other atmospheric stains, allowing them to be washed away with a simple water rinse.

### ADVANTAGES

- An effective, non-acidic restoration cleaning compound.
- Phosphate-free formulation.
- Will not etch glass or metal surfaces.
- Gel-like consistency controls dripping. Material “clings” to vertical surfaces.
- Low-odor and non-fuming – Ideal for interior application.

### Limitations

- May dull or remove waxes or other applied finishes.
- Repeated use may dull polished stonework.

### SAFETY INFORMATION

Always read full label and SDS for precautionary instructions before use. Use appropriate safety equipment and job-site controls during application and handling.

**24-Hour Emergency Information:**  
INFOTRAC at 800-535-5053

### REGULATORY COMPLIANCE

#### VOC Compliance

Sure Klean® Liquid Marble Cleaner is compliant with all national, state and district VOC regulations.

### TYPICAL TECHNICAL DATA

FORM	Orange gel
SPECIFIC GRAVITY	1.13
PH	12.0
WT/GAL	9.4 lbs
ACTIVE CONTENT	not applicable
TOTAL SOLIDS	not applicable
VOC CONTENT	<0.1%
FLASH POINT	>212° F (>100° C) ASTM D 3278
FREEZE POINT	32° F (0° C)
SHELF LIFE	2 years in tightly sealed, unopened container

# Product Data Sheet

## Sure Klean® Liquid Marble Cleaner

### PREPARATION

Protect people, vehicles, property, plants and all surfaces not designated to be cleaned from product, splash, wind drift, residue, and rinse water. Protect/divert auto and foot traffic.

Protect plants and painted surfaces with polyethylene or other proven protective material.

Sure Klean® Strippable Masking is appropriate for use with this product to protect glass and metal.

### Surface & Air Temperatures

Best cleaning results are obtained when air and masonry surface temperatures are 40°F (4°C) or above. To avoid harm to masonry, do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist prior to application, let masonry thaw.

### Equipment

Apply with a soft-bristled brush. Spray application is normally not suitable.

Rinse with fresh water using a sponge or brush, or use pressure-rinsing equipment.

To prevent damage to masonry, use pressure-rinsing equipment generating 400–1000 psi with a water flow rate of 6–8 gallons per minute. Use a 15–45° fan spray tip. Heated water (150–180°F; 65–82°C) may improve cleaning efficiency. Use adjustable equipment for reducing water flow-rates and rinsing pressure as needed for sensitive surfaces.

Rinsing pressures greater than 1000 psi and fan spray tips smaller than 15° may permanently damage sensitive masonry. Water flow-rates less than 6 gallons per minute may reduce cleaning productivity and contribute to uneven cleaning results.

### Storage and Handling

Store in a cool, dry place with adequate ventilation. Keep tightly closed when not dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperature of 45–100° F (7–38° C). Do not double stack pallets. Dispose of unused product and container in accordance with local, state and federal regulations.

### APPLICATION

Read “Preparation” and the Safety Data Sheet before use.

**ALWAYS TEST** a small area of each surface to confirm suitability, coverage rate and desired results before beginning overall application. Include in the test area any previous repairs and patches, including aesthetic cementitious finishes. Different surface compositions may result in absorption and/or appearance differences. Test each type of masonry and each type of stain. Test with the same equipment, recommended surface preparation and application procedures planned for general application. On older masonry, test pressure-rinse as well. Let surface dry thoroughly before inspection.

### Dilution & Mixing

Do not alter or use for purposes other than specified.

For heaving soiling, use in concentrate.

For light soiling, dilute with up to 3 parts water.

### Typical Coverage Rates

Coverage varies based on surface texture, surface porosity, weather conditions at the time of application and the severity of soiling. Always test. Do not over apply.

- 1-gallon of *undiluted* product treats 75–200 sq.ft. (7–19 sq.m.)

### Application Instructions

1. Liberally apply cleaner to the surface using a soft-bristled brush.
2. Leave the cleaner on the surface for 15–20 minutes. Do not let the gel dry on the surface.
3. Rinse the surface thoroughly with fresh water using sponges, brush and bucket, or low-pressure rinsing. Change rinse water frequently. Thorough rinsing is extremely important to ensure all residues are removed from the surface.

### Cleanup

Clean tools and equipment with soap and water.

# Product Data Sheet

## Sure Klean® Liquid Marble Cleaner

### WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

### BEST PRACTICES

ALWAYS TEST for best coverage rates and to confirm results before overall application. Test using the application instructions included herein. Let the test area dry thoroughly before inspection.

Cleaning when temperatures are below freezing or will be overnight may harm masonry. If freezing conditions existed, allow masonry to thaw and warm before application.

When diluting Liquid Marble Cleaner, always pour cold water into an empty bucket first, then carefully add product concentrate. Never use hot water.

Never go it alone. If you have problems or questions, contact your local PROSOCO distributor or field representative. Or call PROSOCO technical Customer Care at 800-255-4255.

### CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care – technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our website at [www.prosoco.com](http://www.prosoco.com), for the name of the PROSOCO representative in your area.

