SAFETY DATA SHEET



Issuing Date 06-Jan-2015 Revision date 12-Nov-2020

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Sure Klean® Weather Seal Gloss 'N Guard

Other means of identification

Product Code(s) 55085 UN number UN1866

Recommended use of the chemical and restrictions on use

Recommended use Restricted to professional users.
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

PROSOCO, Inc. 3741 Greenway Circle Lawrence, Kansas 66046

Emergency telephone number

8:00 AM – **5:00** PM CST Monday-Friday 785-865-4200 NON-BUSINESS HOURS (INFOTRAC) 800-535-5053

2. HAZARDS IDENTIFICATION

Classification

Reproductive toxicity	Category 2
Aspiration hazard	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Warning

Hazard statements

Suspected of damaging fertility or the unborn child May be fatal if swallowed and enters airways Flammable liquid and vapor





Appearance clear Physical state Liquid Odor Mild Petroleum

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/ and /equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

- May be harmful in contact with skin
- · Causes mild skin irritation

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%	Trade Secret
Mineral Spirits	64742-88-7	30 - 60	*
Stoddard Solvent	8052-41-3	10 - 30	*
Proprietary - Acrylic Polymer	Undisclosed	10 - 30	*
1,2,4-trimethylbenzene	95-63-6	3 - 7	*
Nonane	111-84-2	1 - 5	*
Xylene	1330-20-7	1 - 5	*
Toluene	108-88-3	0.1 - 1	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin Contact Wash off immediately with plenty of water. Remove contaminated clothing and shoes. If

skin irritation persists, call a physician.

Inhalation Move to fresh air in case of accidental inhalation of vapors or decomposition products. If

symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Never give anything by mouth

to an unconscious person. Call a physician or poison control center immediately.

Self-protection of the first aider Remove

Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO2). Water spray (fog). Alcohol resistant foam.

Unsuitable Extinguishing Media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas. Pay attention to flashback. Take precautionary measures against static discharges. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later

disposal.

Methods for cleaning upDam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled

containers. Use clean non-sparking tools to collect absorbed material. Take precautionary

measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks,

flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid

breathing vapors or mists.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated

place. Keep away from heat. Keep out of the reach of children.

Incompatible materials Incompatible with oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Stoddard Solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m³	IDLH: 20000 mg/m³ Ceiling: 1800 mg/m³ 15 min TWA: 350 mg/m³
1,2,4-trimethylbenzene 95-63-6			TWA: 25 ppm TWA: 125 mg/m³
Nonane 111-84-2	TWA: 200 ppm	(vacated) TWA: 200 ppm (vacated) TWA: 1050 mg/m ³	TWA: 200 ppm TWA: 1050 mg/m ³
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m³	-
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m³ STEL: 150 ppm STEL: 560 mg/m³

NIOSH IDLH Immediately Dangerous to Life or Health

Other information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state

Liquid

AppearanceClearOdorMild Petroleum

Color Slight yellow Odor threshold No information available

ASTM D 2369

PropertyValuesRemarks • MethodpHNot ApplicableNot Applicable

Melting point / freezing point °F

Boiling point / boiling range

Not Applicable

-30 °C / -22 °F

No information available

Flash point 39 °C / 102 °F

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Specific gravity 0.825 Water solubility negligible

Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Incompatible with oxidizing agents.

Hazardous decomposition products

Carbon oxides. Hazardous combustion products.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Aspiration hazard May be fatal if swallowed and enters airways

Inhalation Avoid breathing vapors or mists. Harmful by inhalation.

Eye contact Avoid contact with eyes. May cause irritation.

Skin Contact Avoid contact with skin. May cause irritation.

Ingestion Do not taste or swallow. May be fatal if swallowed.

Component Information

	oomponone information						
Chemical name		LD50/Oral	LD50/Dermal Inhalation LC50				
	Mineral Spirits	> 25 mL/kg (Rat)	> 3000 mg/kg (Rabbit)	> 13 mg/L (Rat) 4 h			

64742-88-7			
1,2,4-trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg(Rabbit)	= 18 g/m³ (Rat) 4 h
Nonane 111-84-2			= 3200 ppm (Rat) 4 h
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May be fatal if swallowed and enters airways. May cause irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

	Chemical name	ACGIH	IARC	NTP	OSHA
Ī	Xylene	-	Group 3	-	-
	1330-20-7		•		
Ī	Toluene	-	Group 3	-	-
	108-88-3		·		

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5800 mg/kg
ATEmix (dermal) 3226 mg/kg mg/l
ATEmix (inhalation-dust/mist) 19.6 mg/l
ATEmix (inhalation-vapor) 865 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Mineral Spirits 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static	-	100: 48 h Daphnia magna mg/L EC50
1,2,4-trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	-	6.14: 48 h Daphnia magna mg/L EC50
Xylene 1330-20-7	-	13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 7.711 - 9.591: 96 h Lepomis	-	0.6: 48 h Gammarus lacustris mg/L LC50 3.82: 48 h water flea mg/L EC50

		macrochirus mg/L LC50		
		static 13.4: 96 h Pimephales		
		promelas mg/L LC50		
		flow-through 19: 96 h		
		Lepomis macrochirus mg/L		
		LC50 780: 96 h Cyprinus		
		carpio mg/L LC50		
		semi-static 780: 96 h		
		Cyprinus carpio mg/L LC50		
Toluene	12.5: 72 h	11.0 - 15.0: 96 h Lepomis	-	5.46 - 9.83: 48 h Daphnia
108-88-3	Pseudokirchneriella	macrochirus mg/L LC50		magna mg/L EC50 Static
	subcapitata mg/L EC50	static 14.1 - 17.16: 96 h		11.5: 48 h Daphnia magna
	static 433: 96 h	Oncorhynchus mykiss mg/L		mg/L EC50
	Pseudokirchneriella	LC50 static 15.22 - 19.05: 96		-
	subcapitata mg/L EC50	h Pimephales promelas		
		mg/L LC50 flow-through 5.89		
		- 7.81: 96 h Oncorhynchus		
		mykiss mg/L LC50		
		flow-through 50.87 - 70.34:		
		96 h Poecilia reticulata mg/L		
		LC50 static 12.6: 96 h		
		Pimephales promelas mg/L		
		LC50 static 28.2: 96 h		
		Poecilia reticulata mg/L		
		LC50 semi-static 5.8: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 semi-static 54: 96 h		
		Oryzias latipes mg/L LC50		
		static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
1,2,4-trimethylbenzene	3.63
95-63-6	
Xylene	2.77 - 3.15
1330-20-7	
Toluene	2.7
108-88-3	

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesDisposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene	-	Included in waste stream:	-	U239
1330-20-7		F039		
Ethylbenzene	-	Included in waste stream:	-	-
100-41-4		F039		
Cumene	-	-	-	U055
98-82-8				
Toluene	U220	Included in waste streams:	-	U220

108-88-3	F005, F024, F025, F039,	
	K015, K036, K037, K149,	
	K151	

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene	-	-	Toxic waste	-
108-88-3			waste number F025	
			Waste description:	
			Condensed light ends, spent	
			filters and filter aids, and	
			spent desiccant wastes from	
			the production of certain	
			chlorinated aliphatic	
			hydrocarbons, by free	
			radical catalyzed processes.	
			These chlorinated aliphatic	
			hydrocarbons are those	
			having carbon chain lengths	
			ranging from one to and	
			including five, with varying	
			amounts and positions of	
			chlorine substitution.	

14. TRANSPORT INFORMATION

DOT Not regulated (If shipped in NON BULK packaging by ground transport)

UN number UN1866 UN proper shipping name UN1866 Resin Solution

Transport hazard class(es) 3
Packing group |||

IATA

UN number UN1866 UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group

IMDG

UN number UN1866
UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
1,2,4-trimethylbenzene - 95-63-6	95-63-6	3 - 7	1.0
Xylene - 1330-20-7	1330-20-7	1 - 5	1.0
Ethylbenzene - 100-41-4	100-41-4	0.1 - 1	0.1

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	X
Toluene 108-88-3	1000 lb	X	X	X

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Toluene	1000 lb 1 lb	-	RQ 1000 lb final RQ
108-88-3			RQ 454 kg final RQ RQ 1 lb final
			RQ
			RQ 0.454 kg final RQ

US State Regulations

California Proposition 65

This product is not available in California

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Stoddard Solvent 8052-41-3	Х	Х	X
1,2,4-trimethylbenzene 95-63-6	X	X	X
Nonane 111-84-2	X	X	X
Xylene 1330-20-7	Х	X	X
Ethylbenzene 100-41-4	Х	Х	X
Cumene 98-82-8	Х	Х	Х
Toluene 108-88-3	Х	Х	X

16. OTHER INFORMATION

NFPA Health hazards 2 Flammability 2 Instability 0 Physical and chemical

properties -

Health hazards 2 Flammability 2 Physical hazards 0 Personal protection X

Prepared By Regulatory Department

Issuing Date 06-Jan-2015 Revision date 06-Jan-2020

Revision Note

SDS sections updated 1

Disclaimer

The information contained on the Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

End of Safety Data Sheet