SAFETY DATA SHEET



Issuing Date 21-Nov-2014 Revision date 27-Feb-2024

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Sure Klean® Weather Seal H40 Water Repellent

Other means of identification

Product Code(s) 40080 UN number UN1866

Recommended use of the chemical and restrictions on use

Recommended use Restricted to professional users.
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

PROSOCO, Inc. 3741 Greenway Circle Lawrence, Kansas 66046

Emergency telephone number

8:00 AM – **5:00** PM CST Monday-Friday 785-865-4200 NON-BUSINESS HOURS (INFOTRAC) 800-535-5053

2. HAZARDS IDENTIFICATION

Classification

| Serious eye damage/eye irritation | Category 2 |
|-----------------------------------|------------|
| Aspiration hazard | Category 1 |
| Flammable liquids | Category 3 |

Label elements

Emergency Overview

Warning

Hazard statements

Causes serious eye irritation May be fatal if swallowed and enters airways Flammable liquid and vapor



Appearance clear Physical state Liquid Odor Mild Petroleum

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/ and /lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

- May be harmful in contact with skin
- Causes mild skin irritation

29% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name | CAS No. | Weight-% | Trade Secret |
|------------------------------------|------------|----------|--------------|
| Heavy Alkylate Naphtha (petroleum) | 64741-65-7 | 30 - 60 | * |
| Ethyl Silicate | 78-10-4 | 5 - 10 | * |
| Isobutyl triethoxysilane | 17980-47-1 | 1 - 5 | * |

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice In case of accident or unwellness, seek medical advice (show directions for use or safety

data sheet if possible).

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin Contact Wash off immediately with plenty of water. If skin irritation persists, call a physician.

Inhalation Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a

physician.

Ingestion Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Never give anything by mouth

to an unconscious person. Call a physician or poison control center immediately.

Self-protection of the first aider Ren

Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms May be fatal if swallowed and enters airways. Causes serious eye irritation. May be harmful

in contact with skin.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO2). Water spray (fog). Alcohol resistant foam.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Caution: Use of water

spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas. Pay attention to flashback. Take precautionary measures against static discharges. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later

disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Use clean non-sparking tools to collect

absorbed material. Pick up and transfer to properly labeled containers. Take precautionary

measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks,

flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Use with local exhaust ventilation. Avoid breathing vapors or

mists. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat. Keep in properly labeled containers. Keep out of the reach of children.

Incompatible materials Incompatible with oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|----------------|-------------|-------------------------------------|---------------------------|
| Ethyl Silicate | TWA: 10 ppm | TWA: 100 ppm | IDLH: 700 ppm |
| 78-10-4 | | TWA: 850 mg/m ³ | TWA: 10 ppm |
| | | (vacated) TWA: 10 ppm | TWA: 85 mg/m ³ |
| | | (vacated) TWA: 85 mg/m ³ | |

NIOSH IDLH Immediately Dangerous to Life or Health

Other information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations

Ventilation systems. Ground/bond container and receiving equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

ASTM D 3278

provided in accordance with current local regulations.

General Hygiene Considerations Regular cleaning of equipment, work area and clothing is recommended. When using do

not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid
Appearance clear

Appearance clear Odor Mild Petroleum

Color Slight yellow Odor threshold No information available

Property Values Remarks • Method

pH Not Applicable
Melting point / freezing point °F -30 °C / -22 °F

Boiling point / boiling rangeNo information available **Flash point**No information available
37.2 °C / 99 °F

Evaporation rate

Flammability (solid, gas)

No information available
No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available
No information available

Specific gravity 0.882 Water solubility negligible

Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Incompatible with oxidizing agents.

Hazardous decomposition products

Carbon oxides. Hazardous combustion products. Unidentified organic compounds. silicon dioxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation Avoid breathing vapors or mists.

Eye contact Severely irritating to eyes.

Skin Contact May be harmful in contact with skin.

Ingestion Do not taste or swallow. May be fatal if swallowed.

Component Information

| Chemical name | LD50/Oral | LD50/Dermal | Inhalation LC50 |
|--------------------------------------------------|--------------------|-------------------------|-----------------------|
| Heavy Alkylate Naphtha (petroleum) 64741-65-7 | > 7000 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 5.04 mg/L (Rat) 4 h |
| Ethyl Silicate 78-10-4 | = 6270 mg/kg (Rat) | = 5878 mg/kg (Rabbit) | < 1837 ppm (Rat) 4 h |
| Isobutyl triethoxysilane 17980-47-1 | > 5000 mg/kg (Rat) | | > 13750 mg/m³(Rat)4 h |

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May be fatal if swallowed and enters airways. Causes eye irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA,

IARC or NTP.

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown acute toxicity 29% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 5252 mg/kg
ATEmix (dermal) 3479 mg/kg mg/l
ATEmix (inhalation-dust/mist) 10.1 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

| Chemical name | Algae/aquatic plants | Fish | Toxicity to | Crustacea |
|--------------------------|-----------------------|----------------------------|----------------|--------------------------|
| | | | microorganisms | |
| Heavy Alkylate Naphtha | 30000: 72 h | - | - | 2: 48 h Mysidopsis bahia |
| (petroleum) | Pseudokirchneriella | | | mg/L LC50 |
| 64741-65-7 | subcapitata mg/L EC50 | | | _ |
| Ethyl Silicate | - | 245: 96 h Danio rerio mg/L | - | - |
| 78-10-4 | | LC50 semi-static | | |
| Isobutyl triethoxysilane | - | 85: 96 h Oncorhynchus | - | - |
| 17980-47-1 | | mykiss mg/L LC50 | | |
| | | semi-static | | |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesDisposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

14. TRANSPORT INFORMATION

DOT Non-Hazardous/Non-Regulated (Under 119 Gallons per container)

UN number UN1866
UN proper shipping name Resin Solution

Transport hazard class(es) 3
Subsidiary class III
Packing group III

<u>IATA</u>

UN number UN1866 UN proper shipping name Resin Solution

Transport hazard class(es) 3
Subsidiary hazard class III
Packing group III

IMDG

UN number UN1866 UN proper shipping name Resin Solution

Transport hazard class(es) 3
Subsidiary hazard class III
Packing group III

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations. Part 372

SARA 311/312 Hazard Categories

Acute health hazardYesChronic Health HazardNoFire hazardYesSudden release of pressure hazardNoReactive HazardNo

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

| Chemical name | New Jersey | Massachusetts | Pennsylvania |
|----------------|------------|---------------|--------------|
| Ethyl Silicate | X | X | X |

| 78-10-4 | | | |
|---------|---|---|---|
| Ethanol | X | X | X |
| 64-17-5 | | | |

16. OTHER INFORMATION

NFPA Health hazards 3 Flammability 2 Instability 0 Physical and chemical

properties -

HMIS Health hazards 3* Flammability 2 Physical hazards 0 Personal protection X

Prepared By Regulatory Department

Issuing Date 21-Nov-2014 Revision date 27-Feb-2024

Revision Note

SDS sections updated 9 14

Disclaimer

The information contained on the Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

End of Safety Data Sheet