SAFETY DATA SHEET



Issuing Date 21-Nov-2014 Revision date 07-Jun-2022

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Sure Klean® Weather Seal Natural Stone Treatment

Other means of identification

Product Code(s) 40057 UN number UN1866

Recommended use of the chemical and restrictions on use

Recommended use Restricted to professional users.
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

PROSOCO, Inc. 3741 Greenway Circle Lawrence, Kansas 66046

Emergency telephone number

8:00 AM – 5:00 PM CST Monday-Friday NON-BUSINESS HOURS (INFOTRAC)785-865-4200
800-535-5053

2. HAZARDS IDENTIFICATION

Classification

Aspiration hazard	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Warning

Hazard statements

May be fatal if swallowed and enters airways

Flammable liquid and vapor





Appearance clear Physical state Liquid Odor Mild Petroleum

Precautionary Statements - Prevention

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

40057 Sure Klean® Weather Seal Natural Stone Treatment

Use explosion-proof electrical/ventilating/ and /lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

- · May be harmful in contact with skin
- Causes mild skin irritation

10% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%	Trade Secret
Heavy Alkylate Naphtha (petroleum)	64741-65-7	60 - 100	*
Isobutyl triethoxysilane	17980-47-1	1 - 5	*
Ethyl Silicate	78-10-4	1 - 5	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice Immediate medical attention is required. In case of accident or unwellness, seek medical

advice (show directions for use or safety data sheet if possible).

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If skin irritation persists, call a physician.

Inhalation Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a

physician.

Ingestion Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Never give anything by mouth

to an unconscious person. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms May be fatal if swallowed and enters airways. Mild skin irritant. May be harmful in contact

with skin.

Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO2). Water spray (fog). Alcohol resistant foam.

Unsuitable Extinguishing Media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas. Pay attention to flashback. Take precautionary measures against static discharges. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Should not be released into the environment. Prevent product from entering drains. See

Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later

disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Use clean non-sparking tools to collect

absorbed material. Pick up and transfer to properly labeled containers. Take precautionary

measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks,

flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use personal protective equipment

as required. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from heat. Keep

in properly labeled containers. Keep out of the reach of children.

Incompatible materials Incompatible with oxidizing agents.

Mild Petroleum

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl Silicate	TWA: 10 ppm	TWA: 100 ppm	IDLH: 700 ppm
78-10-4		TWA: 850 mg/m ³	TWA: 10 ppm
		(vacated) TWA: 10 ppm	TWA: 85 mg/m ³
		(vacated) TWA: 85 mg/m ³	

NIOSH IDLH Immediately Dangerous to Life or Health

Other information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations

Ventilation systems. Ground/bond container and receiving equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

ASTM D 3278

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid
Appearance clear Odor

Color Slight yellow Odor threshold No information available

PropertyValuesRemarks • MethodpHNot ApplicableNot Applicable

pH Not Applicable
Melting point / freezing point °F -30 °C / -22 °F

Melting point / freezing point °F -30 °C / -22 °F

Boiling point / boiling range No information available

Flash point 48 °C / 118 °F

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available
No information available

Specific gravity 0.784
Water solubility negligible

Solubility in other solvents

Partition coefficient

No information available
No information available

40057 Sure Klean® Weather Seal Natural Stone Treatment

Autoignition temperature

Decomposition temperature

Kinematic viscosity

Dynamic viscosity

No information available

Explosive propertiesNot Applicable **Oxidizing properties**Not Applicable

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Incompatible with oxidizing agents.

Hazardous decomposition products

Carbon monoxide. Carbon dioxide (CO2). Unidentified organic compounds. silicon dioxide. Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information May be fatal if swallowed and enters airways Mild skin irritant

Inhalation Avoid breathing vapors or mists.

Eye contact Avoid contact with eyes. May cause irritation.

Skin Contact Avoid contact with skin. May be harmful in contact with skin. Causes mild skin irritation.

Ingestion Do not taste or swallow. Harmful if swallowed. Potential for aspiration if swallowed.

Component Information

Component information				
Chemical name	LD50/Oral	LD50/Dermal	Inhalation LC50	
Heavy Alkylate Naphtha (petroleum) 64741-65-7	> 7000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.04 mg/L (Rat)4 h	
Isobutyl triethoxysilane 17980-47-1	> 5000 mg/kg (Rat)		> 13750 mg/m³(Rat)4 h	
Ethyl Silicate 78-10-4	= 6270 mg/kg (Rat)	= 5878 mg/kg (Rabbit)	< 1837 ppm (Rat) 4 h	

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May be fatal if swallowed and enters airways. May be harmful in contact with skin. Causes

mild skin irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

40057 Sure Klean® Weather Seal Natural Stone

Treatment

Germ cell mutagenicity No information available.

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA,

IARC or NTP.

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown acute toxicity 10% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 6737 mg/kg
ATEmix (dermal) 2101 mg/kg mg/l
ATEmix (inhalation-dust/mist) 107.5 mg/l
ATEmix (inhalation-vapor) 1120.3 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Heavy Alkylate Naphtha	30000: 72 h	-	-	2: 48 h Mysidopsis bahia
(petroleum)	Pseudokirchneriella			mg/L LC50
64741-65-7	subcapitata mg/L EC50			
Isobutyl triethoxysilane	-	85: 96 h Oncorhynchus	-	-
17980-47-1		mykiss mg/L LC50		
		semi-static		
Ethyl Silicate	-	245: 96 h Danio rerio mg/L	-	-
78-10-4		LC50 semi-static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

14. TRANSPORT INFORMATION

DOT Non-Hazardous/Non-Regulated (Under 119 Gallons per container)

UN number UN1866

40057 Sure Klean® Weather Seal Natural Stone Treatment

UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group III

IATA

UN number UN1866 UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group III

IMDG

UN number UN1866 UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group |||

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazardYesChronic Health HazardNoFire hazardYesSudden release of pressure hazardNoReactive HazardNo

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Ethyl Silicate	X	X	X
78-10-4			

16. OTHER INFORMATION

NFPA Health hazards 3 Flammability 2 Instability 0 Physical and chemical

properties -

HMIS Health hazards 3 Flammability 2 Physical hazards 0 Personal protection X

Prepared By Regulatory Department

Issuing Date 21-Nov-2014
Revision date 07-Jun-2022

Revision Note

SDS sections updated 6 7 11

Disclaimer

The information contained on the Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

End of Safety Data Sheet