

➔ SURE KLEAN® Weather Seal SL100 Water Repellent

"neat" silane water repellent for masonry & concrete

OVERVIEW

Sure Klean® Weather Seal SL100 is a modified, "neat" silane system that offers invisible protection and low volatility. SL100 protects horizontal and vertical concrete and masonry surfaces against water and waterborne contaminants. The small molecular structure ensures maximum penetration and colorless protection of dense, color-sensitive surfaces. Ideal for GFRC, integrally colored precast concrete and many types of natural stone.

The absence of a solvent carrier enables applicators to achieve up to 5 times the coverage rate normally achieved with solvent-reduced protective treatments. Depth of penetration is controlled by the application rate (loading rate).

SPECIFICATIONS

For all PROSOCO product specifications visit www.prosoco.com.

ADVANTAGES

- Excellent surface beading/stain resistance when compared with conventional "neat" silane systems.
- Long-lasting protection.
- Does not form a film or gloss.
- Treated surfaces "breathe" – does not trap moisture.
- Forms an effective chloride screen that reduces surface erosion and corrosion of rebar in reinforced concrete caused by water and water-carried salts.
- Leaves little or no residue on clean window glass. Always test.
- Safe for use on surfaces subjected to vehicle traffic.
- Complies with all known national and state AIM VOC regulations and building codes.
- CALGreen compliant.

Limitations


- Not suitable for asphalt or other non masonry materials.
- Not effective on limestone or marble. Always test natural stone to ensure desired results.
- Not recommended for below-grade applications or for use under hydrostatic pressure.
- Will not prevent water penetration through structural cracks, defects or open joints.
- Not available in South Coast Air Quality Management District, except in regulation-exempt small container sizes.

REGULATORY COMPLIANCE

VOC Compliance

Sure Klean® Weather Seal SL100 Water Repellent is compliant with the following national, state and district regulations:

- US Environmental Protection Agency
- California Air Resources Board SCM Districts
- South Coast Air Quality Management District
- Maricopa County, AZ
- Northeast Ozone Transport Commission



SEALANT • WATERPROOFING & RESTORATION INSTITUTE

Issued to: PROSOCO Inc.
Product: Sure Klean Weather Seal SL 100 Water Repellent

ASTM D 6532: Water Absorption Reduction – Concrete 90%

ASTM C 67: Water Absorption Reduction – Brick 96.5%

ASTM C 140: Water Absorption Reduction – CMU 92.6%

ASTM D 6490: Water Vapor Transmission WVT (grains/h ft²) 1.14; Permeance 2.77

Validation Date: 4/3/13 – 4/2/18

No. 413-SL100418 Copyright © 2013

CLEAR PENETRATING VERTICAL WATER REPELLENT VALIDATION PROGRAM
www.swronline.org

NOTE: The SWR Institute Validation Program uses standardized testing for validation purposes, including testing on CMU. PROSOCO does not recommend the use of SL100 on CMU.

TYPICAL TECHNICAL DATA

FORM	clear to slight yellow liquid
SPECIFIC GRAVITY	0.920
pH	Not applicable
WT/GAL	7.65 lbs
ACTIVE CONTENT	98%
TOTAL SOLIDS	62% ASTM D 5095
VOC CONTENT	350 g/L maximum Reactive Penetrating Sealer
FLASH POINT	94° F (34° C) ASTM D 3278
FREEZE POINT	No data
SHELF LIFE	2 years in tightly sealed, unopened container

➔ SURE-KLEAN® Weather Seal SL100 Water Repellent

PRODUCT DATA SHEET
PROSOCO
SINCE 1939

PREPARATION

Protect people, vehicles, property, plants and all non masonry surfaces from product, splash, residue, fumes, mists and wind drift. Divert and/or protect auto and pedestrian traffic.

Surfaces should be thoroughly clean and free of dust, surface dirt, oil, grease and other contaminants that might prevent penetration. Carefully inspect for dust, dirt, moisture or other contaminants that can cause the product to react and stain the material. Surfaces to be treated may be damp but should be absorbent for good penetration.

Ensure fresh air entry and cross ventilation during application and drying. Extinguish all flames, pilot lights and other potential sources of ignition during use and until all vapors are gone. When applying to exteriors of occupied buildings, make sure all windows, exterior intakes and air

conditioning vents are covered and air handling equipment is shut down during application and until all vapors have dissipated.

If possible, install all caulking, patching and joint sealants before application. If impractical, test for adhesion and grind joints as required to properly prepare for caulking, etc.

New concrete should be thoroughly cured before application.

Specifier's Note – Curing New Concrete:

Blanket or water curing is recommended whenever possible. If a chemical curing agent is to be used during installation of new concrete, a test area is recommended just before general application to ensure compatibility. Dissipating-type curing agents are recommended. Do not over apply the curing agent. Removal of all surface films and contaminants is necessary for best performance.

ALWAYS TEST

ALWAYS TEST a small area of each surface to confirm suitability and desired results before starting overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application.

Equipment

Preferred method of application is with low-pressure (<50 psi) pump type spray equipment. Adjust tip to prevent atomization during application. Battery powered pump sprayers should be rated as explosion proof. Sprayers should be fitted with solvent-resistant hoses and gaskets to avoid discoloration. Do not atomize during application.

Brushes and rollers may not achieve a uniform, extended coverage rate on large-scale applications, which could reduce cost efficiency.

Storage and Handling

Store in a cool, dry place away from potential ignition sources. Keep tightly closed when not dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperature of 45–100°F (7–38°C). Do not double stack pallets. Dispose of unused product and container in accordance with local, state and federal regulations.

NOTE: Some floor and wall systems incorporate asphaltic or other crack-suppression membranes. This deeply penetrative protective treatment may penetrate through exposed stone, tile, grout or paver surfaces and react with the membrane to mobilize objectionable staining. Always pretest to ensure desired results.

Surface and Air Temperatures

For maximum effectiveness, surface and air temperatures should be above 40°F (4°C) and below 95°F (35°C). Application on windy days may cause rapid evaporation and should be avoided.

Recommended for these substrates. Always test.
Coverage is in sq.ft./m. per gallon.

Substrate	Type	Use?	Coverage
Concrete*	Brick	yes	150–400 sq.ft. 14–37 sq.m.
	Tile	yes	
	Precast Panels	yes	
	Pavers	yes	
	Cast-in-place	yes	
Fired Clay*	Brick	yes	200–500 sq.ft. 19–46 sq.m.
	Tile	yes	
	Terra Cotta	yes	
	Pavers	yes	
Marble, Travertine, Limestone	Polished	no	N/A
	Unpolished	no	N/A
Granite	Polished	yes	1000–1500 sq.ft. 93–139 sq.m.
	Unpolished	yes	300–500 sq.ft. 28–46 sq.m.
Sandstone*	Unpolished	yes	200–400 sq.ft. 19–37 sq.m.
Slate	Unpolished	yes	300–600 sq.ft. 28–56 sq.m.

*May have limited effectiveness on highly porous or neutral pH surfaces.

Always test to ensure desired results.

Coverage estimates depend on surface texture and porosity.

➔ SURE KLEAN® Weather Seal SL100 Water Repellent

PRODUCT DATA SHEET

PROSOCO

SINCE 1939

APPLICATION

Before use, read "Preparation" and "Safety Information."

ALWAYS TEST each type of surface for suitability, and results before overall application. Apply test area using the following application instructions. Let test dry thoroughly before inspection.

Dilution

Use in concentrate. Do not dilute or alter, or use for purposes other than specified.

Application Instructions

Horizontal Surfaces

Apply once using enough material to keep the surface wet approximately 30 to 60 seconds before penetrating. Broom out puddles until they completely penetrate the surface.

Vertical Surfaces

Saturate surface in a single application. Use enough to thoroughly wet the surface. Thoroughly brush heavy runs and drips into the surface.

Dense Surfaces

On dense surfaces apply a single coat. Use enough to completely wet the surface without creating drips, puddles or rundown. Do not over apply. Test for application rate.

Second Coat Application

A second application may be needed on some porous surfaces. Apply the second coat a few minutes after the first coat has penetrated and appears dry. SL100 may have limited effectiveness on highly porous surfaces. Always test.

Drying Time

Protect treated surfaces from rain, foot and vehicular traffic for at least 4 hours after application. SL100 gains its water-repellency properties in 72 hours.

Cleanup

Clean tools and equipment immediately with mineral spirits, denatured alcohol or equivalent cleaning solvent. Remove rundown and spills as soon as possible.

SAFETY INFORMATION

Sure Klean® Weather Seal SL100 Water Repellent evolves an alcohol upon reaction with the treated surface and may cause symptoms typical with organic solvent exposures. This product contains a material that can cause lung damage or impairment if inhaled as an aerosol or fine mist. DO NOT ATOMIZE DURING APPLICATION. This is a flammable material. Use appropriate ventilation, safety equipment and job site controls during application and handling. Read the full label and MSDS for precautionary instructions before use.

First Aid

Ingestion: If swallowed, immediately call a physician, emergency room or poison control center for instruction on safely inducing vomiting. If vomiting occurs, keep head below waist to prevent entry of liquid into lungs.

Eye Contact: Rinse eyes thoroughly for 15 minutes. Get medical assistance if irritation persists.

Skin Contact: Rinse thoroughly. Get medical attention if irritation persists.

Inhalation: Remove to fresh air. Give artificial respiration if not breathing. Get immediate medical attention.

24 Hour Emergency Information:
INFOTRAC at 800-535-5053

BEST PRACTICES

Surface should be clean, dry and absorbent before application. Inspect closely.

Clean soiled surfaces with the appropriate Sure Klean® or Enviro Klean® cleaner before application. Call Customer Care toll-free at 800-255-4255 for recommendations.

Prior to application and drying, ensure fresh air entry and cross ventilation. Extinguish all flames and potential sources of ignition before use and during drying.

Preferred method of application is low-pressure spray equipment. Use a fan-type spray tip and adjust pressure to avoid atomization of the material. Use solvent-resistant fittings. Battery-powered sprayers should be rated "explosion proof."

Clean tools and equipment immediately with mineral spirits or equivalent cleaning solvent. Remove rundown and spills as quickly as possible.

Protect surfaces from rain for at least 4 hours after treatment.

ALWAYS TEST for best coverage rates and to confirm results before overall application. Test using the application instructions included herein. Let the test area dry thoroughly before inspection.

Never go it alone. If you have problems or questions, contact your local PROSOCO distributor or field representative. Or call PROSOCO technical Customer Care, toll-free at 800-255-4255.

➔ SURE-KLEAN® Weather Seal SL100 Water Repellent

PRODUCT DATA SHEET
PROSOCO
SINCE 1939

WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for**

particular purpose. The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care - technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at www.prosoco.com, for the name of the Sure Klean® Weather Seal representative in your area.