



R-GUARD

PEEL AND STICK FLASHING

- SEAMLESS APPLICATION
- VAPOR PERMEABLE
- CAN BE EXPOSED TO RAIN
- SELF-SEALING AROUND FASTENERS
- ASTM 2112 PERFORMANCE
- NFPA 285 TESTED
(National Fire Protection Association)
- LIVING BUILDING CHALLENGE COMPLIANCE
- PHthalate PLASTICIZERS FREE?
- EASY APPLICATION
- HIGH SOLIDS CONTENT
- VOC COMPLIANT
- WIDE APPLICATION TEMPERATURE RANGE
- UV EXPOSURE
- EASY FIELD REPAIR

✓ Seamless with uniform adhesion so no water/air migration paths	✗
✓ Allows for vapor diffusion so that substrate can dry and avoid condensation	✗
✓ Will not wash off wall. Rain will not require replacement or harm curing or bonding of material	✗
✓ Creates gasket condition at fasteners for water tightness ASTM D-1970	✗
✓ Air and Water-tight window rough openings	✗
✓ Code compliant wall assemblies	✗
✓ No Red List Ingredients & Health Product Declaration documents available.	✗
✓ No Environmental Concerns	✗
✓ No special tools, equipment or skills required to apply	✗
✓ No shrinkage	✗
✓ No odor or solvents.	✗
✓ Application surface temps from 32°F to 110°F	✗
✓ Can be exposed to UV up to 12 months. Accommodates schedule delays.	✗
✓ Repair by over coating. Saves cost in the event of recoating	✗