CTP STONE-GRIPTIE

SUBMITTAL

CTP 6100-1 Series Anchor

Type 1: Wind load restraint for one direction loading to hollow and solid back-up. Requires 3/4" Socket and CTP 501 Setting Tool Hollow and Solid Back-Up one directional loading to restrain 1 1/4" Stone Veneer 300 S.S. stone panel to hollow solid back-up Hardware 360 Brass Expander Elements 3/8" Back-Up Hole Diameter Torque: 50-100 in-lbs. 1/4" Washer **Bearing Washer Anchor** Façade Drip Control 1" Minimum Hollow Block Embedment Stainless Steel Pilot Hole Shaft: 304 S.S. Diameter Façade CTP Stone-Grip Tie Countersink Hex Head Diameter or • S.S: ASTM 580A, Type 304; ASTM A-276 surface mount

LENGTH			HEAD STYLE		
5 1/2" (138	mm)	☐ 9 1/2" (238mm)	☐ Hex (as show	n) Other	Color
☐ 6 1/2" (163i	mm) 🔲 8 1/2" (213mm)	Other	☐ Standard ☐	Polished D Powder	Coat Bead Blast
			Other		
SPECIFICATION	IS				T
_			DATE:	APPROVED BY:	DRAWN BY:
☐ 62315-150N350 6100-1 Series Stone Grip Anchor 3/4" SS Hex Head x 3-1/2" SS Shaft CTP-6134-1		SCALE: NTS		REVISED:	
☐ 62315-150N400 6100-1 Series Stone Grip Anchor 3/4" SS Hex Head x 4" SS Shaft CTP-6140-1					
☐ 62315-150N450 6100-1 Series Stone Grip Anchor 3/4" SS Hex Head x 4-1/2" SS Shaft CTP-6144-1					
☐ 62315-150N550 6100-1 Series Stone Grip Anchor 3/4" SS Hex Head x 5-1/2" SS Shaft CTP-6154-1			PROJECT:		
☐ 62315-150N650 6100-1 Series Stone Grip Anchor 3/4" SS Hex Head x 6-1/2" SS Shaft CTP-6164-1			CUSTOMER:		DRAWING NUMBER:

